

The lining for protection from impact wear

# REMALINE 60

Our high-quality **REMALINE** lining offers optimum surface protection for your machines and equipment. You avoid unnecessary costs for maintenance and downtime, thereby increasing the productivity of your equipment many times over.

## Application areas

Thanks to its low-abrasion properties, **REMALINE 60** is especially suitable for protecting against impact and dry wear and, based on this, is frequently used for conveying coal. Furthermore, non-driven pulleys can be vulcanized with **REMALINE 60**.



Transfer point



## Typical fields of use

- Lining for vibration feeders, slides, bunkers, chutes and sieve tubs
- Coating of idler, constriction and bending pulleys for medium to high belt tensions

## Advantages

- Protection from impact wear abrasion caused by dry, sharp-edged material
- Easy and fast installation
- Technical consultation and data available anytime
- ▶ **Increases the efficiency of your equipment**

The lining for protection from impact wear

# REMALINE 60

## Technical properties

<b>Product characteristics</b>	<b>REMALINE 60</b> is a mixture of styrene, butadiene and isoprene rubber with good wear resistance against dry wear and impact.	
	CN bonding layer: <b>REMALINE 60</b> comes equipped with a CN bonding layer which affords the product an extremely good adhesive quality in combination with the <b>REMA TIP TOP</b> adhesive systems.	
<b>Storage stability</b>	Max. 24 months ▶ At 25 °C ± 2 °C with no loss in quality. Subject to DIN regulation 7716.	
<b>Color</b>		black
<b>Polymer</b>	DIN ISO 1629	BR/IR/SBR
<b>Specific weight</b>	DIN EN ISO 1183	1,13 g/cm <sup>3</sup>
<b>Hardness</b>	ISO 868-2003 (DIN 53505)	60 ± 5 Shore A
<b>Abrasion</b>	DIN ISO 4649-2006	90 mm <sup>3</sup>
<b>Resilience elasticity</b>	ISO 4462-1986 (DIN 53512)	45 %
<b>Available sizes*</b>	Standard thickness in mm	3 - 50
	Standard width in mm	1 500 or 2 000

\*Other dimensions available with fabric reinforcement.

**REMALINE 60** is also available with fabric reinforcement.

**REMA TIP TOP GmbH**  
Business Unit Industrie

Gruber Strasse 63  
Phone:  
Fax:  
www.rema-tiptop.com

85586 Pöng/Germany  
+49 8121 707-234  
+49 8121 707-222  
info@tiptop.de

Your local contact:

582 1101 - II.07 Printed in Germany

